

# FICHE TECHNIQUE PRODUIT

[Print](#)

## ▼ 530137 Tork Premium Multipurpose Cloth 530 Blanc Bob U/Wiper pack



Chiffon non-tissé très résistant: épais et absorbant

Résiste à l'eau, aux solvants et détergents

Sa surface à reliefs permet de faire disparaître les tâches de gras et les tâches rebelles

Protège les mains de la chaleur au moment de saisir des casseroles ou des plats chauds, et d'être coupé par des morceaux de métal

Contact alimentaire

### ▼ Information produit

|                            |  |
|----------------------------|--|
| <b>Article</b>             | 530137   |
| <b>int. Nom</b>            | Tork Premium Multipurpose Cloth 530 Blanc Bob U/Wiper pack |
| <b>nat. Nom</b>            | TORK PREMIUM 530 BLANC WIPER PAK                           |
| <b>Pays d'origine</b>      | Suameer  |
| <b>Code douanier</b>       | 56039390   |
| <b>Plis</b>                | 1  |
| <b>Longueur:</b>           | 106.4 [m]  |
| <b>Formats:</b>            | 280  |
| <b>Longueur de format:</b> | 38[cm]   |
| <b>Largeur:</b>            | 32 [cm]  |
| <b>Diamètre:</b>           | 25 [cm]  |
| <b>Grammage</b>            | 80 [g/m <sup>2</sup> ]                                     |
| <b>Type de fibres</b>      | Non tissé  |
| <b>Impression</b>          | No   |
| <b>Couleur</b>             | Blanche  |

### ▼ Spécifications du sous-conditionnement

|                                    |               |
|------------------------------------|---------------|
| <b>Unités/sous-conditionnement</b> | 1             |
| <b>Poids brut</b>                  | 3.077 [kg]    |
| <b>Poids net</b>                   | 2.7238 [kg]   |
| <b>Packaging</b>                   |               |
| <b>EAN</b>                         | 7322540057553 |

### ▼ Spécifications du conditionnement

|                                       |                           |
|---------------------------------------|---------------------------|
| <b>Packaging</b>                      | Carton                    |
| <b>Nombre de sous-conditionnement</b> | 1                         |
| <b>Longueur</b>                       | 264 [mm]                  |
| <b>Largeur</b>                        | 264 [mm]                  |
| <b>Hauteur</b>                        | 335 [mm]                  |
| <b>Volume</b>                         | 0.02335 [m <sup>3</sup> ] |
| <b>Poids brut</b>                     | 3.077 [kg]                |
| <b>Poids net</b>                      | 2.724 [kg]                |
| <b>EAN</b>                            | 7322540057553             |

### ▼ Spécifications de la palette

|                                 |                         |
|---------------------------------|-------------------------|
| <b>Conditionnements/palette</b> | 72                      |
| <b>Couches/palette</b>          | 6                       |
| <b>Volume</b>                   | 1.681 [m <sup>3</sup> ] |



SCA HYGIENE PRODUCTS

Roissypôle – Le Dôme – Bâtiment 7, 95761 Roissy CDG Cedex, France. Tél. : 01 41 84 60 00, Fax : 01 41 84 62 52  
www.tork.fr

# FICHE TECHNIQUE PRODUIT

|                |               |
|----------------|---------------|
| <b>Hauteur</b> | 2160 [mm]     |
| <b>EAN</b>     | 7322540195361 |

## ▼ Données environnementales

Chemical pulp  
Polypropene  
Polyester  
Chemicals

### Chemical pulp

Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

ECF is used in this product.

### Polypropene

Polypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

### Polyester

Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

### Chemicals

Both functional and process chemicals are used. The functional chemical used is wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

Process chemical used is a surfactant.

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.



SCA HYGIENE PRODUCTS

Roissypôle – Le Dôme – Bâtiment 7, 95761 Roissy CDG Cedex, France. Tél. : 01 41 84 60 00, Fax : 01 41 84 62 52  
www.tork.fr